

WHAT IS CLAIMED IS:

1. A liquid supply system which is provided with a liquid supply path to a liquid holding portion holding liquid at the downstream end in the supply
5 direction of liquid and a filter in the liquid supply path and in which the liquid can be supplied from the upstream side of the filter to the downstream side thereof in the vertical direction in the direction of gravity, the system comprising:
- 10 a member for dividing a portion of the filter in contact with the downstream side into a gas holding area and a liquid holding area;
- wherein the gas held in said gas holding area is in communication with gas present between the
15 downstream side of the filter and the liquid holding portion in said downstream end.
2. A liquid supply system according to claim 1, wherein the liquid held in said gas holding area
20 communicates with the liquid in said liquid holding portion thereby enabling reversible movement of the liquid at the upstream side of said filter and the liquid at the downstream side of said filter.
- 25 3. A liquid supply system according to claim 1, wherein the gas present between the downstream side of said filter and the upstream side of the liquid

10066623-020602

holding portion at said downstream end is so positioned as to inhibit movement of a bubble from said liquid holding portion to said filter.

5 4. A liquid supply system according to claim 1, further comprising:

 a liquid connection structure for holding, at the downstream side of said filter in said liquid supply path, the liquid present at the downstream
10 side of said filter across the gap of said gas holding area by the surface tension of said liquid and connecting said liquid with the liquid at the upstream side of said filter.

15 5. A liquid supply system according to claim 4, wherein said liquid connecting structure includes a groove-shaped structure portion which is provided along the vertical direction and of which the upper end is almost in contact with the face of said filter
20 at the downstream side thereof.

 6. A liquid supply system according to claim 5, wherein the gap t between said groove-shaped structure portion and said filter is within a range
25 of $0 \leq t \leq 1.0$ mm.

 7. A liquid supply system according to claim 5,

2090902 020602 1006622

wherein said groove-shaped structure portion has a cross section of recessed shape.

8. A liquid supply system according to claim 5,
5 wherein said groove-shaped structure portion has a cross section of wedge shape.

9. A liquid supply system according to claim 5,
10 wherein said groove-shaped structure portion has an arc-shaped liquid holding surface.

10. A liquid supply system according to claim 5,
wherein said groove-shaped structure portion has a member in which plural hollowing portions for holding
15 liquid are formed, and said member is provided at the downstream side of said filter.

11. A liquid supply system according to claim 5,
wherein said groove-shaped structure portion
20 satisfies a relation $L/S \geq 1000$ wherein L is the circumferential length of an area in contact with the liquid in said groove-shaped structure portion and S is the cross section of an area in contact with the liquid in said groove-shaped structure portion.

25

12. A liquid supply system according to claim 5,
wherein surrounding portion of said groove-shaped

10066622-020602

structure portion is cut off or rounded.

13. A liquid supply system according to claim 5,
wherein said groove-shaped structure portion is
5 integrally constructed with a member constituting
said liquid supply path at the downstream side of
said filter.

14. A liquid supply system according to claim 5,
10 wherein, at the downstream side of said filter, said
liquid supply path includes a cover member
constituting a lateral face of said liquid supply
path and a main body member constituting another face
of said liquid supply path and jointed to said cover
15 member, and said groove-shaped structure portion is
provided at least on said cover member.

15. A liquid supply system according to claim
14, wherein said cover member and said main body
20 member are jointed with adhesive, and the groove-
shaped structure portion provided on said cover
member is provided as a protruding portion with a
slit, protruding from the adhered face of said cover
member with said main body member and holding the
25 liquid by the surface tension thereof.

16. A liquid supply system according to claim

10066623:020602
209020:22999001

15, wherein said protruding portion is provided with a groove for receiving said adhesive between the adhered face of said cover member with said main body member and said slit.

5

17. A liquid supply system according to any of claims 1 to 16, wherein said liquid supply path has a first liquid chamber at the upstream side of said filter and a second liquid chamber including the gas
10 of said gas holding area at the downstream side of said filter.

18. A liquid supply system according to claim 17, wherein said first liquid chamber includes
15 pressure adjusting means for absorbing pressure variation in said first liquid chamber.

19. A liquid supply system according to claim 17, further comprising, at the upstream side of said
20 first liquid chamber in said liquid supply path, a valve structure to be opened at the normal liquid supply state and to be closed at the liquid filling into said second liquid chamber by suction from said downstream end.

25

20. A liquid supply system according to claim 17, wherein said first liquid chamber includes an air

10066623-020602

communication aperture which can be opened and closed and is to be closed at the liquid filling into said second liquid chamber by suction from said downstream end.

5

21. A liquid supply system according to claim 17, further comprising, at the downstream side of said filter in said liquid supply path, a third liquid chamber for holding the liquid in such a manner that the liquid is in contact with a part of the surface of said filter at the downstream side thereof.

22. A liquid supply system according to claim 21, wherein said third liquid chamber includes a structure for holding the liquid by the surface tension thereof in contact with the surface of said filter at the downstream side thereof.

23. A liquid supply system according to claim 22, wherein the structure for causing the liquid of said third liquid chamber to contact the surface of said filter at the downstream side thereof includes at least a rib so provided that the front end thereof is in contact with the surface of said filter at the downstream side thereof.

100666623.020602

24. A liquid supply system according to claim
21, wherein the amount of the liquid that can be held
in said third liquid chamber is larger than the
amount of change in the volume of the gas in said gas
5 holding area anticipated in the environment of use.

25. A liquid supply system according to claim
21, wherein said third liquid chamber is so provided
as to surround an aperture connecting said filter and
10 said second liquid chamber.

26. An ink jet recording head provided with a
first liquid chamber and a second liquid chamber
separated by a filter and respectively containing
15 liquid therein, and a liquid discharge portion
connected directly with said second liquid chamber
and adapted to discharge the liquid supplied from
said second liquid chamber, in which the liquid can
be supplied from said first liquid chamber to said
20 second liquid chamber through said filter,
comprising:

a member for dividing a portion of the filter in
contact with said second liquid chamber into a gas
holding area and a liquid holding area;

25 wherein the gas held in said gas holding area is
in communication with the gas present in said second
liquid chamber.

10066623.020602

27. An ink jet recording head according to claim
26, wherein the liquid held in said liquid holding
area communicates with the liquid in said liquid
chamber thereby enabling reversible movement of the
5 liquid in said first liquid chamber and the liquid in
said second liquid chamber.

28. An ink jet recording head according to
claim 26, wherein the gas present in said second
10 liquid chamber is so positioned as to inhibit
movement of a bubble from said liquid discharge
portion to said filter.

29. An ink jet recording head according to
15 claim 26, further comprising a liquid connection
structure for holding the liquid present in said
second liquid chamber across the gas of said gas
holding area by the surface tension of said liquid
and connecting said liquid with the liquid in said
20 first liquid chamber through said filter.

30. An ink jet recording head according to
claim 29, wherein said liquid connecting structure
includes a groove-shaped structure portion which is
25 provided along the liquid supply direction from said
first liquid chamber to said second liquid chamber
and of which the upper end is almost in contact with

10066623-020602

the surface of said filter at the downstream side thereof.

31. An ink jet recording head according to
5 claim 30, wherein the gap t between said groove-shaped structure portion and said filter is within a range of $0 \leq t \leq 1.0$ mm.

32. An ink jet recording head according to
10 claim 30, wherein said groove-shaped structure portion has a cross section of recessed shape.

33. An ink jet recording head according to
15 claim 30, wherein said groove-shaped structure portion has a cross section of wedge shape.

34. An ink jet recording head according to
claim 30, wherein said groove-shaped structure
portion has an arc-shaped liquid holding surface.

20

35. An ink jet recording head according to
claim 30, wherein said groove-shaped structure
portion has a member in which plural hollowing
portions for holding liquid are formed, and said
25 member is provided at the downstream side of said
filter.

10066623 020602

36. An ink jet recording head according to claim 30, wherein said groove-shaped structure portion satisfies a relation $L/S \geq 1000$ wherein L is the circumferential length of an area in contact with the liquid in said groove-shaped structure portion and S is the cross section of an area in contact with the liquid in said groove-shaped structure portion.

37. An ink jet recording head according to claim 30, wherein surrounding portion of said groove-shaped structure portion is cut off or rounded.

38. An ink jet recording head according to claim 30, wherein said groove-shaped structure portion is integrally constructed with a member constituting said second liquid chamber.

39. An ink jet recording head according to claim 30, wherein said second liquid chamber includes a cover member constituting a lateral face of said second liquid chamber and a main body member constituting another face of said second liquid chamber and jointed to said cover member, and said groove-shaped structure portion is provided at least on said cover member.

40. An ink jet recording head according to

10056623.020602

claim 39, wherein said cover member and said main
body member are jointed with adhesive, and the
groove-shaped structure portion provided on said
cover member is provided as a protruding portion with
5 a slit, protruding from the adhered face of said
cover member with said main body member and holding
the liquid by the surface tension thereof.

41. An ink jet recording head according to
10 claim 40, wherein said protruding portion is provided
with a groove for receiving said adhesive between the
adhered face of said cover member with said main body
member and said slit.

42. An ink jet recording head according to
15 claim 26, wherein said first liquid chamber includes
pressure adjusting means for absorbing pressure
variation in said first liquid chamber.

43. An ink jet recording head according to
20 claim 26, further comprising a connecting portion to
which the liquid supply means to said first liquid
chamber is detachably connected.

44. An ink jet recording head according to
25 claim 26, further comprising, between said first
liquid chamber and said second liquid chamber, a

10056523-020602

third liquid chamber for holding the liquid in such a manner that the liquid is in contact with a part of the surface of said filter at the side of said second liquid chamber.

5

45. An ink jet recording head according to claim 44, wherein said third liquid chamber includes a structure for holding the liquid by the surface tension thereof in contact with the surface of said
10 filter.

46. An ink jet recording head according to claim 45, wherein the structure for causing the liquid of said third liquid chamber to contact the
15 surface of said filter includes at least a rib so provided that the front end thereof is in contact with the surface of said filter at the side of said second liquid chamber.

20 47. An ink jet recording head according to claim 44, wherein the amount of the liquid that can be held in said third liquid chamber is larger than the amount of change in the volume of the gas in said gas holding area anticipated in the environment of
25 use.

48. An ink jet recording head according to

10066623.020602

claim 44, wherein said third liquid chamber is so provided as to surround an aperture connecting said filter and said second liquid chamber.

5 49. An ink jet recording apparatus comprising:
support means for supporting an ink jet recording head according to any of claims 26 to 48;

 suction means for forcedly sucking ink in said ink jet recording head from the liquid discharge portion
10 thereof; and

 a valve mechanism for opening or closing of the first liquid chamber of said ink jet recording head to or from the exterior thereof.

15 50. An ink jet recording apparatus according to claim 49, further comprising:

 an ink supply unit on which an ink tank containing ink is detachably mounted and which serves to supply the ink in said ink tank to said ink jet recording
20 head through a tube;

 wherein said valve mechanism is provided in an ink supply path from said ink tank to said ink jet recording head.

25 51. An ink jet recording head according to claim 49, wherein said first liquid chamber includes an air communicating aperture, and said valve

209020-22999001

mechanism controls to open or close said air communicating aperture.

52. A liquid filling method for use in a
5 liquid supply system in which first and second liquid
chambers respectively holding liquid are separated by
a filter while liquid is held at the downstream side
of said second liquid chamber in the liquid supply
direction from said first liquid chamber to said
10 second liquid chamber, a member is provided for
separating a contact portion of the downstream side
of said filter into a gas holding area and a liquid
holding area in a state capable of liquid supply from
the upstream side of said filter to the downstream
15 side thereof in the vertical direction of gravity,
and the gas held in said gas holding area is in
communication with the gas present between the
downstream side of said filter and the upstream side
of the liquid holding area at said downstream end,
20 the method comprising:

a step of closing the first liquid chamber from
the exterior;

a step of executing suction from the downstream
side of said second liquid chamber in a state where
25 said first liquid chamber is closed, thereby reducing
the pressure of said first and second liquid
chambers; and

10066623-020602

a step, after the pressure reduction of said first and second liquid chambers, of opening said first liquid chamber to the exterior.

10066623.020602